

AireTechnologies, Inc. 1502 Industrial Drive E. Monongahela, PA 15063

phone: 866.421.AIRE fax 724.310.1262

www.airetechnologies.com



Job	
Location	
Submitted to	
Submittal Prepared by	
Approve Date	
Doto	

UL Classified - 1½ Hour Rating, Dynamic For use in installations rated less than 3 hours

Standard Profile (4¼") 22 Ga 1 piece rollformed frame

Type A Damper Blades in air-stream

ഗ

Φ

Q

S

Available for vertical and horizontal installations

For installation in systems where fans remain running during fire and smoke control


Standard fusible link - 165° F (optional 212° F)

Available in stainless steel


Vertical dampers are available in single-section sizes from 4" x 4" to 36" x 36"

Horizontal dampers are available in single-section sizes from 4" x 4" to 24" x 24"

Optional 22 Ga Sleeve available: 8", 12", 17", 20", or 24" lengths (12" is standard)



Fire Damper Series 77 Type A






This product meets the requirements for fire dampers established by:

UL Standards 555 NFPA Standard 90A ICC Building Codes

Qty.	Mount	Damper Size		Fusible Link Temp	
	(V) vertical (H) horizontal	W	Н	(165°F) std.	Factory Sleeve Length

Part Number Format







AireTechnologies, Inc. 1502 Industrial Drive E. Monongahela, PA 15063

phone: 866.421.AIRE fax 724.310.1262