



Series 95

Type B - Thinline Static Fire Damper

Specifications

UL Classification:

UL Classified UL 555 - **3 Hour Rating**, Static For Use in Installations Rated 3 Hours or Greater

Profile:

Thinline Profile - 2" 22Ga 1 Piece Rollformed Frame

Material:

Galvanized Steel - Standard
Stainless Steel - Optional

Blades:

Blades Out Of Air-Stream - Type B Damper

Orientation:

Available For Vertical Installations ONLY

Sizes:

Available In Single-Section Sizes:
Vertical - 4" x 3" to 48" x 41"

Fusible Link:

165° F Rated Link - Standard
212° F Rated Link - Optional

22 Ga Optional Sleeves:

12" Sleeve - Standard
8", 12", 17", 20", or 24" Lengths - Optional

Job: _____


Location: _____

Submitted to: _____

Submittal Prepared by: _____

Approve Date: _____

Date: _____



This product meets the requirements for fire dampers established by:

**UL Standards 555
NFPA Standard 90A
ICC Building Codes**



3225-1650: 0107



Aire Technologies


1502 Industrial Drive, Monongahela, PA 15063

1-866-421-AIRE

atorders@airetechnologies.com

AireTechnologies.com

Part Number Format



Qty.	Mount	Damper Size		Fusible Link Temp (165°F) std.	Factory Sleeve Length
	(V) Vertical	W	H		

